

Pedestal & Wall / Vertical Mounts

Non-Oscillating



1 Year Warranty

Features

- 120V, 1 Phase, 2 Speed, 1/4 HP, Open Ventilated, Ball Bearing Motor
- Permanently lubricated permanent split capacitor
- Pull Chain, SJT type 3 conductor, 9½' long cord
- Pedestal adjusts center of fan from 44" to 62"
- Epoxy coated steel guard with retaining clips
- Wall / Vertical mount includes safety cable
- Meets OSHA Standards
- Aluminum blades



EDP No.	Catalog No.	Prop Dia.	Fan Style	CFM		RPM		F.L. Amps	Ship Wt.
				High	Low	High	Low		
71531	LC30AP	30"	Pedestal Mount	6000	5500	1100	800	2.1	62
71533	LC30WC	30"	Wall / Vertical Mount						37

Because these circulators do not have totally enclosed motors, they should be used in clean and dry commercial applications, such as schools, offices or warehouses.

Belt Drive Portable Mancooler®



1 Year Warranty

Features

- 115V, 1 HP, 1 Phase, 2 Speed, 630 Watts, ODP, Ball Bearing Motor
- Epoxy Coated Steel Guards and Housing
- Aluminum Four Bladed Propeller
- Grounded Plug and 10' Cord
- Full Width Easy Grip Handle
- Two Speed Rocker Switch
- Velocity: 159 fpm @ 90 ft.
- Fully Assembled
- 8" Steel Wheels



EDP No.	Catalog No.	Prop Dia.	HP	CFM		RPM		dBA		Ship Wt.
				High	Low	High	Low	High	Low	
78933	LC42BD	42"	1	13036	11850	582	517	70	66	103



Warning: Cancer and Reproductive Harm www.P65Warnings.ca.gov
This warning is applicable to all products on this page, see page i2 for more information