



## Heavy-Duty Hazardous Location Air Circulators

### Pedestal, Wall, I-Beam & Vertical Mount Fans

Non-Oscillating

115/230V or 230/460V Spark Resistant

Unit Packs 115/230V Spark Resistant Models



1 Year Warranty - Ultra Quiet

#### Features

- 115/230V, 1/4 HP, 1 Phase & 230/460V, 1/4 HP, 3 Phase, Single Speed, Ball Bearing Motors
- A safety cable kit is included in all overhead mounted air circulators to prevent the fan from falling if accidentally struck or mounting fails. Single safety cable kits consist of 12 feet of 1/16" diameter cable, 2 cable clamps and instructions
- OSHA Approved Safety Guards
- Die Cast Aluminum Propeller



#### FOR USE IN HAZARDOUS LOCATION SUCH AS:

Oil Refineries  
Welding Shops  
Paint Operations / Storage and Other Locations that may contain Explosive Gas, Vapor or Dust in the Atmosphere

### 115/230V, 1/4 HP, 1 Phase Models

Motor, Specified Mounting, Propeller & Guard shipped in a single carton

EDP No.	Catalog No.	Prop Dia.	Fan Style	CFM	RPM	Motor No.	F.L. Amps	Ship Weight
20301	UP24LF16X	24"	Pedestal Fan	5739	1140	1169	6.9 / 3.5	93
20321	UP24LW16X8	24"	Wall Mount	5739	1140	1169	6.9 / 3.5	61
20341	UP24LI16X	24"	I-Beam Mount	5739	1140	1169	6.9 / 3.5	65
20331	UP24LS16X	24"	Vertical Mount	5739	1140	1169	6.9 / 3.5	56
20351	UP30LF16X	30"	Pedestal Fan	8723	1140	1169	6.9 / 3.5	98
20371	UP30LW16X8	30"	Wall Mount	8723	1140	1169	6.9 / 3.5	67
20391	UP30LI16X	30"	I-Beam Mount	8723	1140	1169	6.9 / 3.5	70
20381	UP30LS16X	30"	Vertical Mount	8723	1140	1169	6.9 / 3.5	61

Performance Ratings are conducted in accordance with AMCA Standard 230-99. Explosion Proof Motor for Class 1, Group D & Class II, Groups E, F & G. See page 3 for further Explosion Proof Motor information.

### 230/460V, 1/4 HP, 3 Phase, Spark Resistant Models

Motor, Specified Mounting, Propeller & Guard shipped in a single carton

EDP No.	Catalog No.	Prop Dia.	Fan Style	CFM	RPM	Motor No.	F.L. Amps	Ship Weight
20450	24LF36X	24"	Pedestal Fan	5739	1140	1269	1.1 / 0.55	100
20470	24LW36X8	24"	Wall Mount Fan	5739	1140	1269	1.1 / 0.55	79
20490	24LI36X	24"	I-Beam Mount Fan	5739	1140	1269	1.1 / 0.55	79
20480	24LS36X	24"	Vertical Mount Fan	5739	1140	1269	1.1 / 0.55	69
20500	30LF36X	30"	Pedestal Fan	8723	1140	1269	1.1 / 0.55	107
20520	30LW36X8	30"	Wall Mount Fan	8723	1140	1269	1.1 / 0.55	86
20540	30LI36X	30"	I-Beam Mount Fan	8723	1140	1269	1.1 / 0.55	86
20530	30LS36X	30"	Vertical Mount Fan	8723	1140	1269	1.1 / 0.55	76

**NOTES:** X = Explosion Proof. **CORD AND PLUG NOT PROVIDED.** Must be hard wired. Wiring must conform to all national, state and local codes. Performance Ratings are conducted in accordance with AMCA Standard 230-99. Explosion Proof Motor for Class 1, Group D & Class II, Groups E, F & G. See page 3 for further Explosion Proof Motor information.

