


Washdown Air Circulators

Stainless Steel Food Service Air Circulators Unit Pack Models

Non-Oscillating



10 Year Warranty

Features

- 115V, 1/15 HP (20") and 115/230V, 1/4 HP (24"), 1/3 HP (30"), 1 Phase, Totally Enclosed Non-Vented, Ball Bearing Motor
- Constructed with Electro-polished 304 Stainless Steel Meets the USDA and the NSF Requirements for "Food Zones"
- Designed to Withstand Moist/Wet Environments, High Pressure Cleaning with Concentrated Caustic Solutions without Affecting Performance or Function.
- Performance Ratings are conducted in accordance with AMCA Standard 230-99
- · Available in Non-Adjustable Pedestal or Wall Mount
- Motor Washdown Specification is IEC-IP55
- Guards meet OSHA Standards
- All Stainless Steel Motor





EDP No.	Catalog No.	Prop Dia.	Fan Style	НР	CFM		RPM		Motor No.	Chin M/4
					High	Low	High	Low	MOTOL NO.	Ship Wt.
70834	PWIISS20	20"	Floor Model	1/15	2670 1670	4000	4000	ED.	69	
70833	WWIISS20	20"	Wall Model	1/15		1670	1600	1000	5B	52
70836	PWIISS24	24"	Floor Model	1/4	5220		1075		4G	79
70835	WWIISS24	24"	Wall Model	1/4						62
70764	PWIISS30	30"	Floor Model	1/3	8800		1075		4H	81
70767	WWIISS30	30"	Wall Model	1/3						64

Note: When assembling fans use only the stainless steel fasteners supplied with the motors. Fans and motors should be cleaned and inspected regularly. A safety cable kit is included in all overhead mounted air circulators to prevent the fan from falling if accidentally struck or mounting fails. Single safety cable kits consiste of 12 feet of 1/16" diameter cable, 2 cable clamps and instructions.

Chemical Resistance Rating Chart

Chemical	Concentration	Stainless Steel Parts						
Water:								
De-Ionized Boiling	100%	Excellent						
Salt (Immersed)	30%	Excellent						
Salt (Spray)	5%	Excellent						
Tap - 250°/120° @10,000 PSI	100%	Excellent						
Acids:								
Hydrochloric	35%	Poor						
Sulfuric	25%	Poor						
Nitric	35%	Excellent						
Picric	Saturated Solution	Excellent						
Base:								
Caustic	100%	Excellent						
Caustic	12pH	Excellent						
Caustic - 1250 F/500 C	-	Excellent						

FOOD SERVICE DAIRY BARNS
HOSPITALS POULTRY HOUSES

FISHERIES

*CORD AND PLUG NOT PROVIDED WITH 115V or 115/230V MODELS. MUST BE HARD WIRED. WIRING MUST CONFORM TO ALL NATIONAL STATE AND LOCAL CODES

FOOD PROCESSING