

## Heavy Duty Easy Clean Air Circulator

Non-Oscillating



### 2 Year Warranty Features

- 115V, 1/3 HP, 1 Phase, Totally Enclosed Air Over Ball Bearing Motor, Non-Oscillating
- Nickel-Chrome Plated Hinged Guard for ease of cleaning
- Drop Cord Models 2 Speed, Pull Chain Models 3 Speed
- Meets OSHA Safety Standards
- Galvanized Steel Propeller
- 15' Supply Cord Included
- 3 Mounting Options
- 30" Prop Diameter



### 2 Speed Drop Cord Switch

EDP No.	Catalog No.	Fan Style	HP	CFM		RPM		Motor No.	F.L. Amps	Ship Wt.
				High	Low	High	Low			
71503	CA30HGDCS	Head Assembly	1/3	6100	2700	1100	600	642-AC2SDC	2.7	49
71504	CA30HGDCSIB	I-Beam	1/3							65
71506	CA30HGDCSPB	Pedestal	1/3							92
71507	CA30HGDCWM	Wall	1/3							62

### 3 Speed Pull Chain Switch

EDP No.	Catalog No.	Fan Style	CFM			RPM			Motor No.	F.L. Amps	Ship Wt.
			High	Med	Low	High	Med	Low			
71500	CA30HGPC	Head Assembly	6100	4400	2700	1100	800	600	642-AC 3 SP	2.8	49
71501	CA30HGPCWM	Wall									62
71502	CA30HGPCPB	Pedestal									92
71505	CA30HGPCIB	I-Beam									65

### Component Parts

EDP No.	Catalog No.	Fan Style	Ship Wt.
01515	DCD	Dome only for drop cord	2
01633	Cord	15' Power Cord	2
01723	Switch	Switch - Pull Chain	2
01754	Guard-Safety Pin	Safety Pin - 1 only	1
12013	2-SPDCS-HD	End Dome with drop cord and 2 speed switch	2
12015	DCS-2	Drop Cord with 2 speed switch	1
21017	642-AC 3 SP	Pull Chain Motor	19
21089	COM30-HG&P	30" Hinged Guard and Prop - Chrome	32
21090	642-AC2SDC	Drop Cord Motor	19
21152	8CP-2B	Pedestal	13
21166	A786B-2	Solid 32" floor base	34
21187	878W	Tilted Wall Bracket with Safety Cable	10
21191	700-U	I-Beam Bracket with Safety Cable	14
21204	Safety Kit	Safety Cable Kit	1

**Note:** "K" suffix indicates unit shipped as individual component parts. May be shipped UPS or Truck. A safety cable kit is included in all overhead mounted air circulators to prevent the fan from falling if accidentally struck or mounting fails. Single safety cable kits consist of 12 feet of 1/16" diameter cable, 2 cable clamps and instructions