

Commercial Air Circulators - 115V

Pedestal & Wall Mount Unit Packs

Non-Oscillating

2 Year Warranty

Features

- 115V, 1/4 HP, 1 Phase, 3 Speed, TEAO Ball Bearing Motor
- A safety cable kit is included in all overhead mounted air circulators to prevent the fan from falling if accidentally struck or mounting fails. Single safety cable kits consist of 12 feet of 1/16" cable, 2 cable clamps and instructions
- Unit Pack ships with Motor, Specified Style Mounting, Propeller & Guard In One Carton
- Pedestal Models Adjust 43" - 63" ; 26" Base Diameter
- Wall Mount Models Include Safety Cable
- 15' Supply Cord and Three Prong Plug Included
- Models are UPS Shippable in One Carton
- Guard Meets OSHA Standards
- Galvanized Steel Propeller
- All Stocked

Wall Mount




Type	Tilt (In Degrees) Non-Oscillating	
	Up	Down
Floor	30°	15°
Wall	30°	50°

Adjustable Floor Model

EDP No.	Catalog No.	Prop Dia.	Fan Style	HP	CFM			RPM			F.L. Amps	Ship Wt.
					High	Med	Low	High	Med	Low		
71584	CA24APE	24"	Adjustable Floor	1/4	4400	3460	2460	1100	800	600	3.5	82
71572	CA24WC	24"	Wall Mount	1/4								42
71586	CA30APE	30"	Adjustable Floor	1/4	6100	4400	2700	1100	800	600	3.5	87
71573	CA30WC	30"	Wall Mount	1/4								49
71760	UPI-24PA2A	24"	Adjustable Floor	1/3	5520	4020	2820	1080	700	540	3.0	81
71725	I-24W2A	24"	Wall Mount	1/3								44
71526	UPI-30PA2A	30"	Adjustable Floor	1/3	7185	5300	3415	1080	700	540	3.0	90
71726	I-30W2A	30"	Wall Mount	1/3								49

Non-Oscillating Assembled Fan Heads



Features

- Motor, Guard, and Propeller are Pre-Assembled
- 30" Head Assembly is UPS OverSize 2
- Vertical Mount Option Available with Head Assemblies

EDP No.	Catalog No.	Prop Dia.	HP	Ship Wt.
37113	I-18TEHA	18"	1/15	24
37114	I-20TEHA	20"	1/15	27
71590	CA24	24"	1/4	39
71591	CA30	30"	1/4	48
37209	I-24	24"	1/3	37
71591	I-30	30"	1/3	48

