



Mark 2

Continuous Duty

Features

Units must be mounted where the blades are at least 10' from the floor

MARK 2

- 120 V, 1 phase
- Electro-Static Paint
- Highest efficiency in its class
- 3 blade, aluminum
- 8828 minimum CFM
- Full Load Amps 1.87
- Includes Safety Cable and J Hook for easy Installation
- 1 Year Commercial Warranty
- UL / CUL Listed
- Non Reversible



120V Model Ceiling Fans

EDP No.	Description	Color	Prop Dia.	Down Length*	RPM	Ship Wt.
40139	Mark 2*	White	55"	15"	282	15

- Recommended for quiet applications, such as churches or schools, when using Variable Speed Control as produces least audible harmonics.

Accessories for 120V Models Only

EDP No.	Description	Ship Wt.
24855	Variable Speed Control Regulates up to 2 fans. Not to exceed a maximum amp draw of 6.0	1
24860	Variable Speed Control Regulates up to 6 fans. Not to exceed a maximum amp draw of 12.0	1
24880	Humiditat 20% to 80% RH range.	1

Accessories for all Ceiling Fans

EDP No.	Description	Ship Wt.
09019	J-Hook & Safety Cable <i>(recommended for EDP#40139)</i>	1
40006	UCFG Protective Ceiling Fan Guard - 61" diameter nickel chrome plated top and bottom guard kit.	21
21204	Safety Cable Kit for Retrofit Applications	3

