

## Pedestal or Wall Mount Non-Oscillating

### 3 Year Warranty Features



**Adjustable Floor**

- 115/230V, 1/4 HP (24"), 1/3 HP (30"), 1 Phase, Totally Enclosed Non-Vented, Ball Bearing Motor
- Wall Mount is supplied with the required Safety Cable Kit.
- Nickel Chrome Guard Meets OSHA Standards
- 15' Three Conductor Supply Cord and Plug
- Galvanized Steel Propeller
- UPS Shippable - All Parts Packaged in One Extra Large Carton - Surcharge May Apply
- Designed to Withstand Moist/Wet Environments, High Pressure Cleaning with Concentrated Caustic Solutions without Affecting Performance or Function.
- BISSC / ANSI/ASB/Z50.2-2015 sanitation standard
- Available in Non-Adjustable Pedestal or Wall Mount
- All Parts Packaged in One UPS shippable carton
- Motor Washdown Specification is IEC-IP55
- All Stocked



**Wall Mount**

Type	Tilt (In Degrees) Oscillating	
	Up	Down
Floor	30°	20°
Wall	0°	20°

0° = Horizontal Plane

EDP No.	Catalog No.	Prop Dia.	Fan Style	CFM			RPM			Motor Number	F.L. Amps	Ship Wt.
				High	Med	Low	High	Med	Low			
71761	I-24-WDPNO	24"	Pedestal Fan	5548	4699	4062	1110	958	856	0-3B	3.2	86
71763	I-24-WDWNO	24"	Wall Mount									57
71762	I-30-WDPNO	30"	Pedestal Fan	7794	5943	5143	1091	871	759	0-3B	3.2	95
71764	I-30-WDWNO	30"	Wall Mount									61
73301	I-24WDP	24"	Replacement Prop									5
73401	I-30WDP	30"	Replacement Prop									5

Performance Ratings are conducted in accordance with AMCA Standard 230-99



**Warning:** Cancer and Reproductive Harm [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)  
This warning is applicable to all products on this page, see page i2 for more information